Project:		Date
Type:		
Model#		

MWR-MWS LED Bollards

PRODUCT DESCRIPTION

The Moon Walk Series features a heavy-cast aluminum housing designed with modern aesthetics in mind. The architectural luminaire provides brilliant illumination to walkways and other outdoor spaces, improving the visibility, safety, and overall look of any outdoor area. Powered by energy-saving LED technology, this high-powered outdoor luminaire is Dark Sky compliant and paired with state-of-the-art optics to restrict light trespass, glare and light pollution for neighborhood-friendly outdoor lighting.



S = Square



R = Round

PRODUCT SPECIFICATIONS

- Efficacy: 90 LPW
- Delivered Light Output: 900 - 2,700 Lumens
- Watts: 10W, 20W, 30W
- CRI: Ra>70
- CCT: 3000K, 4000K, 5000K
- Input Voltage: 120-277VAC
- Power Factor: 0.95
- Operating Temperature: -31°F ~ 113°F
- Dimming: Non Dimmable
- Standard Warranty: 5 Years
- Standard Lifetime: Designed to L70 minimum 50,000 hours
- IP Rating: IP65
- Materials: Steel base / powder coating

ORDER INFORMATION

EXAMPLE: MWR-36-30W-Y-40K-T5-29-BK

Series	Size	Watts	Voltage	CCT	Optics	Mount	Finish
MWR=Round MWS=Square	18in 24in 36in 42in	10W 20W 30W	Y=120-277V HV=480V**	30K = 3000K 40K = 4000K 50K = 5000K AMB = Amber	3M 5M	29=Anchor Bolts	SL = Silver BZ = Bronze BK = Black WH = White


Enter configuration: _____

** Special Order / contact vendor

Series / Performance

Series No.	MWR/MWS-10W	MWR/MWS-20W	MWR/MWS-30W
Power	10W	20W	30W
Lumens:	900	1,800	2,700
Efficacy	90 LPW	90 LPW	90 LPW
Input current 120/277V	0.08 / 0.03 Amps	0.16 / 0.07 Amps	0.25 / 0.10 Amps
Input	120-277V AC	120-277V AC	120-277V AC

Dimensions



Photometric Data

