

Project:	Date
Туре:	
Model#	

VPS2 Series LED Vapor Tight

PRODUCT DESCRIPTION

The Luminoso VPS Series is a versatile, linear fixture that can be used in a number of applications. It's IP65 and IK09 rated exterior makes it ideal for interior or exterior uses such as parking areas, corridors, warehouses/factories, airports, and supermarkets. It's tough exterior is only rivaled by its cutting edge technology. Utilizing only the highest grade LED arrays the VPS series boasts lumen outputs of 130 lumens per watt. It is available in either 4000K or 5000K color temperatures with lengths ranging from 2' to 4' and wattages ranging from 30 watts to 60 watts.

3.5"

23.6"

PERFORMANCE SUMMARY

Dimmable: No

Efficacy: 130 Lm/W	0100
Delivered Light Output: 3,872 - 3,900	0
Lumens Input Power: 30 Watts	
CRI: 80	VPS2 Dimensions
CCT: 4000K & 5000K	
Input Voltage: 100-277vAC	-
Input Current: .0.18 A (@277v)	(
Beam Angle: 120°	
THD: 18%	
Power Efficiency: >0.88	
Construction Material: Polycarbonate	
Warranty: 5 years	
Power Factor: 0.9	
IP Rating: IP65	
Lifespan: L70 50,000 hours	



ORDER INFORMATION

EXAMPLE: VPS2-14-30W-40K-J-Y-FR

Series	Mount	Wattage	CCT	Optics	Voltage	Lens	Fixture Options
VPS2	14= Direct Mount 23= Hanging Kit	30W	40K = 4000K 50K = 5000K	J=120°	Y=120-277V	FR=Frosted	RF= Rear Power Feed EF= End Power Feed 3HK = 3 Meter Hanging Kit** 5HK = 5 Meter** Hanging Kit

Enter configuration:

** Special Order / Contact vendor






Series / Performance

Series No.	VPS2-30W
Power	30W
Lumens	3,800 (40K) / 3,900 (50K)
Net Weight	25.8 lb
Gross Weight	29.5 lb
Dimensions (L x W x H)	23.6 x 3.5 x 2.4 in
Input	120-277V AC
Max Connection Quantity.	600W on a single AC input.

Photometry - Luminous Intensity Distribution Diagram



Standard Accessories

Length for power cord or connection cable can be Customized.



