

UDFP-54W Series Linear LED Suspension

Project: _____

Type: _____


Model# _____

PRODUCT DESCRIPTION


The 1' x 4' Up/Down LED suspension fixture utilizes an advanced LED optical system. Suspended from the ceiling, this innovative beautiful luminaire combines brilliant aesthetics with perfect uniformity of light – no visible diodes or glare. The optics create the illusion of the light floating in mid-air, and provides 55% down lighting and 45% up light distribution. Included is a UL Recognized constant current driver with 0-10V dimming and step dimming, capabilities.

PERFORMANCE SUMMARY

Efficacy: 109-112 LPW
Delivered Light Output: 5,906 - 6,025 Lumen
Power: 54 Watts
CRI: 80
CCT Options: 3500K, 4000K, 5000K
Input Voltage: 120-277 VAC
Input current: 0.55A
THD:<20%
Driver output: DC36-42V 580mA
Standard Warranty: 5 Year Warranty
Standard Lifetime: Designed to L70 minimum 50,000 hours
Installation: Suspended
Continuous run on one feed, when connecting together: 6pcs Max (120V)
0-10V dimming
Dimensions: L 47.24" x W 11.81" x H 1.06"



DIMENSIONS



EXAMPLE: UDFP-23-54W-40K-E-Y



Series	Mount	Wattage	CCT	Beam	Voltage
UDFP	23 Hanging Kit	54W	35K: 3500K 40K: 4000K 50K: 5000K	E 115°	Y 120-277V

Enter configuration: _____


UDFP Series Product Performance & Photometry

Performance Summary


Model	Watts	CCT	Lumen (Lm)	Efficacy	CRI	Beam (angle°)	Voltage	Operating Temp.
UDFP	54W	3500K	5,906	109 LPW	80	115°	120-277VAC 50/60Hz	-4°F to 113°F
		4000K	5,966	110 LPW				
		5000K	6,025	112 LPW				

PHOTOMETRY

Fixture photometry has been conducted in accredited testing laboratory in accordance with IESNA LM-79-08.



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.