

Project:		Date
Type:		
Model#		

DCOV Series Linear LED Light

PRODUCT DESCRIPTION

The Luminoso DCOV Series is a sleek, multi-function, linear fixture that can be used in a wide range of applications. It can be used as a low profile fixture for general lighting or as a cove light to create a beautiful, evenly dispersed, ambient light. The DCOV series is available in 2, 3, and 4 foot lengths and in either 3000K, 4000K, or 5000K color temperatures. With lumen packages ranging from 1,650 to 3,300 lumens, this versatile product can be the answer to many difficult lighting scenarios.

FEATURES

LED Chip

The active color management system maintains superior color consistency over time. Every fixture is tuned as a complete system to the optimal color point before shipment, ensuring consistent fixture to fixture color.

Heat Sink

The thermal management system's cooling design allows for even heat dispersion which minimizes heat concentration. This enables the LEDs to consistently run cooler, providing significant boosts to lifetime, efficacy, and color consistency.

Optical System

Proprietary optical system utilizes a unique combination of reflective and refractive optical components to achieve a uniform, comfortable appearance. Using high density laser pixels to emit even light. This product produces no glare.



Flex Connector



Connector

Standard Accessories



ORDER INFORMATION

EXAMPLE: DCOV3-14-25W-30K-J-Y-FR

Series	Watts	CCT	Voltage	Dimension (L x W x H)
DCOV2-14-15W-XX-J-Y-FR	15W	3000K / 4000K / 5000K	110-277V	21.9 x 1.6 x 1.4
DCOV3-14-25W-XX-J-Y-FR	25W	3000K / 4000K / 5000K	110-277V	33.5 x 1.6 x 1.4
DCOV4-14-30W-XX-J-Y-FR	30W	3000K / 4000K / 5000K	110-277V	45.2 x 1.6 x 1.4





Enter configuration:

** Special Order / contact vendor

Series / Performance

Series No.	DCOV2	DCOV3	DCOV4
Power	15W	25W	30W
Lumens	1,650	2,750	3,300
Efficacy	110 (Lm/W)	110 (Lm/W)	110 (Lm/W)
Input	100-277V	100-277V	100-277V
CRI	80	80	80
Standard Lifetime	L70 minimum 50,000	L70 minimum 50,000	L70 minimum 50,000
Operating Temperature	-4°F to 122°F	-4°F to 122°F	-4°F to 122°F
Dimmable	TRIAC	TRIAC	TRIAC

Dimensions



Linkable up to 200 Watts

