



## LED EMERGENCY LIGHT







# **BUG EYE 2 SQUARE HEADS**

## **FEATURES:**

- Injection-molded thermoplastic ABS housing
- UL-94V-0 flame rating, fire-retardant
- · Wall mounting
- Input Voltage: 120/277VAC 60Hz
- Standard LED 2x1.2W
- Nickel Cadmium Battery
- · Test button and charge indicator light
- Backup time: ≥90minutes
- · Conversion time: <0.2second
- IP Class: IP20
- Insulation: II, Range: 8m²
- Operating Temperature: 14°F to104°F
  Overcharge & Over-discharge protection
- Dimension: 13.6 x 4.1 x 3.1 IN

#### HOUSING

Injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white finish. Aesthetically pleasing, curved face, rounded corner design. Test switch provided.

#### MOUNTING

EZ-snap mounting canopy included for top or end mount. Universal K/O pattern on back plate for wall mount.

## WARRANTY

5 year limited warranty on all electronics and housing. Battery pro-rated for five years.

**EXAMPLE:** LE-BPL-2S-W-N

Series	LED Light	Finish	Battery	Listings
LE-BPL	2S 2LT Square	<b>W</b> White	N Nickel-cadmium batteries	
				(LED) (UL)

Enter configuration:

11.01.2018.2 luminosoled.com

