

Product Description

The Luminoso MWPK Series combines traditional styling with the latest LED technology. The high pressure die cast housing along with anti-static powder painting makes this product ideal for exterior applications. The MWPK's highly efficient cooling system allows lower running temperatures translating into a maximized product life. The wall pack has a built in UL class driver and is also rated for damp and wet locations. Ideal for entry ways, area perimeters, stairwells and hallways this product offers the added security and cost effectiveness to meet any demand.

Features

Efficacy: 107 - 121 Lm/W
 Power consumption: 15, 17, 25 Watts
 Delivered Light Output: 1,600 - 2,700 Lumens
 CRI: Ra>70
 CCT: 3000K, 4000K, 5000K
 Input Voltage: 120 - 277 VAC
 Input current: 0.33 - 0.14 Amps (120-277V)
 THD: <20% (at 120V)
 Power factor: > 0.9 (120V)
 Lens: Polycarbonate optical lens
 Mounting: J-Box or Direct wall mount w/ 1/2" entry at the bottom
 Non-dimmable
 Standard Lifetime: Designed to L70 minimum 50,000 hours
 Operating temperature is -40°F to 104°F).

Project:	Date
Type:	
Model:	



ACCESSORIES

Photocell

No. PC-JL-120-277V
 USE: Photocell is field installed or pre-installed in factory by requesting



ORDER INFORMATION

EXAMPLE: MWPK-14-17W-40K-3M-Y-BZ



Series	Mount	Wattage	CCT	Optics	Voltage	Finish	Photocell	Lens
MWPK Wall Pack	14 Direct Mount	15W	30K 3000K	3M	Y 120-277V	WH White	Blank Standard	Blank Clear
		17W	40K 4000K			BZ Bronze	PC (120-277V)	FR Frosted
		25W	50K 5000K					

Enter configuration:

** Special Order

PERFORMANCE DATA

SYSTEM WATTS	VOLTAGE	LENS	CRI	LUMENS (3000K)	LPW (3000K)	LUMENS (4000K)	LPW (4000K)	LUMENS (5000K)	LPW (5000K)
15W	120-277VAC	Clear Lens	70	1,600lm	107 lm/W	1,700lm	113 lm/W	1,750lm	117 lm/W
		Frosted Lens	70	1,760lm	117 lm/W	1,800lm	120 lm/W	1,820lm	121 lm/W
17W	120-277VAC	Clear Lens	70	1,800lm	106 lm/W	1,900lm	112 lm/W	1,950lm	115 lm/W
		Frosted Lens	70	1,900lm	112 lm/W	2,000lm	118 lm/W	2,020lm	119 lm/W
25W	120-277VAC	Clear Lens	70	2,500lm	100 lm/W	2,550lm	102 lm/W	2,600lm	104 lm/W
		Frosted Lens	70	2,550lm	102 lm/W	2,600lm	104 lm/W	2,700lm	108 lm/W

DIMENSIONS

