

# **VPS LED Vapor Tight**

2FT & 4 FT Vapor Tight

#### PRODUCT DESCRIPTION

The Luminoso VPS Series is a versatile linear fixture suitable for a wide range of applications. With an IP66 and IK10 rating, it thrives in both interior and exterior settings like parking areas, corridors, warehouses, factories, airports, and supermarkets. Its robust build is matched only by its cutting-edge technology, utilizing premium LED arrays for an impressive 130 lumens per watt output. Available in 4000K or 5000K color temperatures, with lengths from 2 to 4 feet and wattage options of 30 to 50 watts.

# **SPECIFICATION FEATURES**

SI LUII IUNIIUN I LAIUNLS
Efficacy: 110-130 Lm/W
Delivered Light Output: 3,750 to 6,200 Lumens
CCT: 4000K, 5000K
Wattage: (2FT) 30W / (4FT) 40W, and 50W
CRI: Ra>80
Input Voltage: 120-277 VAC
Input current: 0.4 - 0.17A
THD: <19% (120V)
Power Factor >0.95 (120V)
Frequency: 50/60Hz
Standard Warranty: 5 Years
Standard Lifetime: Designed to L70 minimum 50,000 hours
Mounting: Direct Mount or Suspension kit available
Dimming: Not dimmable
IP Rating: IP66
Operating temp: -4°F to 122°F

Project:	Date
Туре:	
Model:	





#### ORDER INFORMATION

EXAMPLE: VPS4-40W-Y-40K-J-14-FR













Series	Wattage	Voltage	ССТ	Beam	Mount	Lens	Motion Sensor
VPS2 2FT Vapor Tight	30W 30 Watts	<b>Y</b> 120-277V	<b>40K</b> 4000K	J 120°	14 Direct Mount	FR Frosted	<b>Blank</b> No Sensor
VPS4 4FT Vapor Tight	<b>40W</b> 40 Watts		<b>50K</b> 5000K		<b>3HK</b> 3 Meter Suspension Kit		MS Motion Sensor
	<b>50W</b> 50 Watts		For 3000K contact vendor		<b>5HK**</b> 5 Meter Suspension Kit		

Enter configuration:

\*\* Special Order


Dimensions and values shown are nominal. LuminosoLED continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.




# PERFORMANCE DATA

Model	Voltage	Power	CCT	CRI	Max Lumen	Lifetime	Dimension	Carton Size	Qty/CTN
VPS2-2FT		30W			3,800 / 3,900		23.6 x 3.5 x 2.4 in	37.6 x 8.1 x 8.7 in	
VPS4-4FT	120-277V	40W	40K / 50K	>80	4,962 / 5,200	50,000 hrs	47.2 x 3.5 x 2.4 in	37.6 x 8.1 x 8.7 in	6
VPS4-4FT		50W			6,000 / 6,200		47.2 x 3.5 x 2.4 in	57.1 x 8.1 x 8.7 in	

# **DIMENSIONS**





# **ACCESSORIES**

LC (Link Cable)



6IN-LC (6 in) 1M-LC (1 Meter) 2M-LC (2 Meter)

Mounting Clips included



1M-PC (1 Meter) 2M-PC (2 Meter)

PC (Power Cable)

# Mounting Screws included

