DL 2HD RS CCTS

2 INCH LED ROUND SMOOTH MODULE-TRIM / CCT SELECTABLE

Project:

Type:

Model:

DESCRIPTION

The Luminoso LED trims are designed for use with Luminoso 2" dedicated housings. Now CCT selectable, the 2" LED trim is the perfect solution for low to medium-height ceilings in residential and light commercial applications. Its small aperture makes it ideal for strategic placement where space is limited, while offering flexibility in color temperature selection and maximizing energy savings.

ELECTRICAL

Current : 350mA


LED ENGINE

CCT Selectable: 2700K, 3000K, 3500K, 4000K, 5000K
Wattage: 8W
Optics: 90°

FEATURES

LED Life: 50,000 Hours
Operating Temperature: -22°F to 113°F
Warranty: 5 year limited warranty
IP54 Rated
Dims down to 10% with TRIAC









BK - Black



BZ - Bronze

Watts	CRI	CCT Selectable	Lumens	Input Voltage	Frequency
8W	90	2700K 3000K 3500K 4000K 5000K	710 740 770 780 760	120VAC	50/60Hz

Compatible Housings (Order Separately)	Rating	Model	Installation	Input	Dimming
	IC-Rated	DLH 2TD N 23 Z ICQA	New Construction	120VAC	TRIAC
	IC-Rated	DLH 2TD R 23 Z ICQA**	Remodel	120VAC	TRIAC

Example: DL-2HD-RS-23-8W-CCTS-Z-WH

Series	Trim	Mount	Watts	CCT Selectable	Voltage	Finish
DL 2HD	**RS** Round Smooth	**23** Quick Connect	**8** 8 Watts	**CCTS** (Color Temp. Selectable) 27K / 30K / 35K / 40K / 50K	**Z** 120VAC	**WH** White **BZ** Bronze** **BK** Black**

Enter configuration:

** Contact vendor for lead time.


Dimensions and values shown are nominal. LuminosoLED continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.

PHOTOMETRY / 3000K

DL 2HD RS

System Power	:8.8W
Test Date	:3/2016
Beam Angle 50% Field Angle 10%	:36.2º :65.3º
Color Temperature	:3000K
CRI	:90. 0
R9 Value	:73. 0
Lumens Delivered	:680Lm
CBCP	:1,494cd
Power Factor	:0.89

CANDELA TABULATION



FOOTCANDLE DISTRIBUTION

Height	Beam Diameter	FC
8.0’	5.2’	23.3
10.0’	6.5’	14.9
12.0’	7.8’	10.4
16.0’	10.5’	5.8
20.0’	13.1’	3.7