

Project: _____
 Type: _____
 Model: _____

DESCRIPTION

The Luminoso 2" LED New Construction housing is perfect for low to medium height ceilings in commercial applications. The air tight construction reduces energy costs by preventing air flow between occupied conditioned spaces and unvented areas.

HOUSING

Integral thermal protector to guard against improper lamping and installation. Trim is secured with internal locking mechanism. Galvanized steel construction.

DRIVER

120-277V built in electronic Direct Current U.L. Listed driver mounted away from LED Array for cool operation and end-of-life modularity. The Luminoso 2" housing and trim combination are standard with 0-10V dimming.

BAR HANGER

Pre-installed nails, easily installs in regular lumber and engineered lumber. Bar Hangers are adjustable from 13-5/8" to 25" and can be repositioned 90 degree on plaster frame.

FEATURES


- UL Listed for Damp Locations
- UL Listed for Feed Through
- Warranty: 5 year limited warranty
- Certified under ASTM-E283 for Air Tight Construction
- Built in Driver 120-277V (0-10V dims down to 10%)




Dimensions and values shown are nominal. LuminosoLED continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.




COMPATIBLE TRIMS




DL 2HD RS



DL 2HD RG



DL 2HD SS



DL 2HD SG

DIMENSIONS

