

DESCRIPTION

The YHB High Bay is a flexible and efficient lighting solution available in three sizes to suit a wide range of applications. It features built-in lumen and CCT selectability, allowing you to customize light output and color temperature from a single fixture. With high efficacy options of 169 lm/W, the YHB delivers powerful, energy-efficient illumination. A standard 0-10V sensor port enables easy plug-and-play sensor integration, and an optional emergency battery backup provides added reliability. Engineered for performance, adaptability, and long-term durability, the YHB High Bay is the ideal choice for high-performance lighting in any environment.

FEATURES

Construction

- Die-cast aluminum housing and heatsink to optimize thermal transfer and maximize performance of the LEDs.

Optics

- Achieves efficiency levels of up to **169lm/W**
- 150W & 240W replaces 250-400W MH.
- Offers standard 4000K and 5000K light modules.
- >80 CRI
- Provides even light intensity with a 120-degree lens.

Electrical

- Universal voltage of 120-277VAC or 480VAC (50/60Hz)
- 0-10V dimming standard for a dimming range of 100% to 10%.
- Functions in temperatures ranging from -40°C (-40°F) to 50°C (122°F)
- All models are designed to withstand up to 6kV surge.

Controls

- Optional Microwave sensor or PIR sensor.*


Lifespan

- Estimated 50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

Project:	Date
Type:	
Model:	



DIMENSIONS



WS150

WS240

ORDER INFORMATION

EXAMPLE: YHB-WS150-Y-CCTS-WH



Series	Wattage Selectable	Voltage	CCTS	Motion Sensor	Finish	Safety Chain	Emergency Battery Backup	Reflector
YHB High Bay light	WS150 (150W / 100W / 80W)	Y 120-277V	CCTS (4000K / 5000K)	(Blank) Standard no sensor	WH White	(Blank) Standard	(Blank) Standard	(Blank) Standard
	WS240 (240W / 200W / 150W)	HV 480V		MS PIR Motion Sensor	BK Black	SC Safety Chain	EB Emergency Battery Back-up	PCR PC Reflector


Enter configuration:

Dimensions and values shown are nominal. LuminosoLED continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.

PERFORMANCE DATA

Series	YHB 150W			YHB 240W		
Wattage Selectable	150W / 100W / 80W			240W / 200W / 150W		
Dual CCT Selectable	4000K / 5000K			4000K / 5000K		
Lumens	(23,250) / (16,350) / (13,550)	(22,650) / (15,950) / (13,200)	(37,450) / (31,800) / (25,300)	(36,240) / (30,800) / (24,500)		
Efficacy (LPW)	155LPW / 164LPW / 169LPW	151LPW / 160LPW / 165LPW	156LPW / 159LPW / 169LPW	151LPW / 154LPW / 164LPW		
Beam	Narrow - Medium - (Standard) Wide			Narrow - Medium - (Standard) Wide		
Input Voltage	120-277VAC & 480V / 50/60Hz			120-277VAC & 480V / 50/60Hz		
Certifications	UL Listed, FCC, RoHS			UL Listed, FCC, RoHS		
Operating Temp.	-13°F to 122°F			-13°F to 122°F		
PF / THD	>0.9, <20%			>0.9, <20%		
Dimming	0-10V (10%-100%)			0-10V (10%-100%)		

Wattage & CCT Selectable (Built in switches)



ACCESSORIES (Reflector / Emergency Battery Backup)




Polycarbonate Reflector




Emergency Battery Backup
25W / 90min / AC120-277


PHOTOMETRICS



Wide



Medium (Standard)



Narrow