

Project:	Date
Type:	
Model:	

DESCRIPTION

This FLM2 LED flood light features field-selectable wattage and three selectable CCT options, allowing for flexible performance and simplified inventory. It delivers a lumen output range of 7,800 to 28,000 lumens, providing reliable, energy-efficient illumination for a wide range of outdoor applications.

Construction

- Sealed die-casting profile for outdoor applications.
- Casting thermally conducts LED heat to optimize performance and long life.
- Vented housing separates the LED module from the driver to enhance longevity and performance.

Optics


- Selectable color temperature 3000K/4000K/5000K.
- Adjustable lumen output with four lumen settings 100%, 80%, 60%, 40%.
- Scalable Lumen Packages from 7,800 to 28,000 Lumens.
- High performance UV stabilized optical grade polymer refractor lenses to achieve desired distribution.
- NEMA Type 7Hx6V

Electrical

- Universal 120-277 VAC input voltage.
- Not dimmable.
- Both drivers have a power factor >90%, THD <20%.
- Operating Temperature Range: -40°C to 40°C (-40°F - + 104°F).

Controls

- Optional photocell



ORDER INFORMATION

EXAMPLE: FLM2-WS60-Y-CCTS-KN-BK



Series	Wattage Selectable	Voltage	CCTS	Mounting Options	Photocell	Finish	
FLM2 Flood Light	WS60 (60W / 48W / 36W / 24W)	Y 120-277V	CCTS Selectable Color Temperature (3000K / 4000K / 5000K)	SF Slipfitter (100W/200W only)*	Blank Standard	BZ Bronze	
	WS100 (100W / 80W / 60W / 40W)			TR Trunnion (100W/200W only)*			PC Photocell
	WS200 (200W / 160W / 120W / 80W)			YK Yoke (60W only)*			
				KN* Knuckle (60W only)*			

Enter configuration: _____

Dimensions and values shown are nominal. LuminosoLED continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.

FLM2 Flood Light

Specifications & Measurements



PERFORMANCE


		FLM2 60W					
SETTING	WATTAGE	3000K (70CRI)		4000K (70CRI)		5000K (70CRI)	
		LUMENS	LPW	LUMENS	LPW	LUMENS	LPW
100%	60W	7,800lm	130 lm/W	8,400lm	140 lm/W	8,100lm	135 lm/W
80%	48W	6,480lm	135 lm/W	7,000lm	146 lm/W	6,700lm	140 lm/W
60%	36W	5,050lm	140 lm/W	5,400lm	150 lm/W	5,250lm	146 lm/W
40%	24W	3,480lm	145 lm/W	3,720lm	155 lm/W	3,600lm	150 lm/W

		FLM2 100W					
SETTING	WATTAGE	3000K (70CRI)		4000K (70CRI)		5000K (70CRI)	
		LUMENS	LPW	LUMENS	LPW	LUMENS	LPW
100%	100W	13,000lm	130 lm/W	14,000lm	140 lm/W	13,500lm	135 lm/W
80%	80W	10,800lm	135 lm/W	11,600lm	146 lm/W	11,200lm	140 lm/W
60%	60W	8,400lm	140 lm/W	9,000lm	150 lm/W	8,700lm	145 lm/W
40%	40W	5,800lm	145 lm/W	6,200lm	155 lm/W	6,000lm	150 lm/W

		FLM2 200W					
SETTING	WATTAGE	3000K (70CRI)		4000K (70CRI)		5000K (70CRI)	
		LUMENS	LPW	LUMENS	LPW	LUMENS	LPW
100%	200W	26,000lm	130 lm/W	28,000lm	140 lm/W	27,000lm	135 lm/W
80%	160W	20,800lm	135 lm/W	23,200lm	146 lm/W	22,400lm	140 lm/W
60%	120W	16,800lm	140 lm/W	18,000lm	150 lm/W	17,400lm	146 lm/W
40%	80W	11,600lm	145 lm/W	12,400lm	155 lm/W	12,000lm	150 lm/W


DIMENSIONS

60W (Knuckle)




Net Weight
60W: 3.152 lb

100W (Slipfitter)




Net Weight
100W: 10.163 lb

200W (Slipfitter)




Net Weight
200W: 15.146 lb

60W (Yoke)




Net Weight
60W: 3.748 lb

100W (Trunnion)



Net Weight
100W: 9.237 lb

200W (Trunnion)



Net Weight
200W: 15.146 lb




FLM2 Flood Light

Mounts / EPA / Photometrics

MOUNTING



EPA

Item							
	1	2 @90°	2 @120°	2@180°	3 @90°	3 @120°	4 @90°
100W	0.2885	0.6097	0.7475	0.577	0.8982	0.8196	0.8982
200W	0.3868	0.8125	0.9973	0.7736	1.1993	1.0874	1.1993

PHOTOMETRIC

7HX6V

100W、200W、350W

