

4" Round Dome Downlight/Surface

Project: _____

Type: _____

Model#: _____

DESCRIPTION

4" surface mount/recessed LED trim, is compatible with most 4" new construction and remodel housings. Universal mounting hardware allows mounting to all standard 4 inch junction boxes. Optional Recessed Housing Adapter available.

PRODUCT SPECIFICATIONS

- White painted stamped aluminum body.
- Oversized trim ring.
- 3 Tension clips per-installed on unit for easy installation.
- E26 medium screw-base Edison adapter provides easy installation into Incandescent housings.
(GU10 and GU24 socket adapter available - sold separately)

LED LIGHT ENGINE

- Protected LED driver performs at 120-277V.
- Dimming down to 5% with most TRIAC / CL dimmers (@120V)
- CCT: 3000K & 4000K available
- Operating Temperature: -15°F to 104°F
- Long life LED chips guaranteed up to 50,000 hours.

LISTINGS

- UL classified
- Suitable for wet locations.
- Suitable for use in closets, compliant with NFPA® 70
- Tested in accordance with IESNA LM79 & LM80

PERFORMANCE DATA

CCT	Lumens	Watts	CRI	Input Voltage	Frequency
3000K	880 Lm	10W	90	120-277V	50/60Hz
4000K	900 Lm				




Series	Reflector	Mount	Watts	CCT	Beam	Voltage
DL-4	RD = Round Dome	23 J-Box or E26	10W	30K = 3000K 40K = 4000K	120°	Y = 120-277VAC

Enter configuration: _____




DIMENSIONS



ACCESSORY KIT



J - Box Installation



Can Installation

