

PRODUCT DESCRIPTION

Our popular vapor tight just got better! The VPR2 now features CCT and Wattage Selectable switch. Our low profile design makes it a perfect replacement for T8 and T5 fixtures. Its wide distribution angle is ideal for lighting applications such as garages, stairwells, warehouses, manufacturing and service areas. Lastly, the VPR2 series' exceptional 50,000+ hours of operation and wattage reductions of over 50% from its traditional counterparts makes it a truly revolutionary product.

SPECIFICATION FEATURES

Efficacy: 140-148 Lm/W
Delivered Light Output: 2,800 to 10,500 Lumens
CCT Selectable: 3500K, 4000K, 5000K
Wattage Selectable
CRI: Ra>80
Input Voltage: 120-277 VAC
Input current: 0.4 -0.17A
THD: <20% (120V)
Power Factor >0.95 (120V)
Frequency: 50/60Hz
Standard Warranty: 5 Years
Standard Lifetime: Designed to L70 minimum 50,000 hours
Mounting: Direct Mount
Dimming: 0-10v dimming, 10%-100% smooth linear dimming
IP Rating: IP66
Operating temp: -40°F to 104°F

Project:	Date
Type:	
Model:	



Bottom



Top



ORDER INFORMATION

EXAMPLE: VPR2-4-WS-CCTS-Y-FR



Series	Wattage Selectable	CCT Selectable	Voltage	Lens
VPR2 Vapor Tight	2-WS 2FT Vapor tight (20W / 17W / 14W)	CCTS Selectable Color Temperature (3500K / 4000K / 5000K)	Y Y = 120-277V	FR Frosted
	4-WS 4FT Vapor tight (36W / 30W / 24W)			
	5-WS 5FT Vapor tight (65W / 54W / 38W)			
	8-WS 8FT Vapor tight (75W / 65W / 42W)			

Enter configuration:

Dimensions and values shown are nominal. LuminosoLED continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.

PERFORMANCE DATA

Model	Voltage	Power	CCT	CRI	Max Lumen	Lifetime	Dimension	Carton Size	Qty/CTN
VPR2-2FT	120-277V	20W / 17W / 14W	35K / 40K / 50K	>80	2,800	50,000 hrs	25.6 x 3.9 x 3.4 in	26.4 x 11.5 x 9.1 in	6
VPR2-4FT	120-277V	36W / 30W / 24W	35K / 40K / 50K	>80	5,040	50,000 hrs	47.7 x 3.9 x 3.4 in	48.5 x 8.9 x 8 in	4
VPR2-5FT	120-277V	65W / 54W / 38W	35K / 40K / 50K	>80	9,230	50,000 hrs	59.5 x 3.9 x 3.4 in	60.1 x 9 x 8.5 in	4
VPR2-8FT	120-277V	75W / 65W / 42W	35K / 40K / 50K	>80	10,500	50,000 hrs	94.9 x 3.9 x 3.4 in	95.7 x 8.9 x 4.4 in	2



DIMENSIONS

