




DL3 RB 3" Round Baffle Trim



DL3 RS 3" Round Smooth Trim

Dimensions



Descriptions

The Luminoso LED retrofit trims are designed for use with Luminoso 3" Dedicated housings and are compatible with most 120V housings with 3" openings.

LED Driver • Built-in

- Dimmable down to 5% with TRIAC Dimmers
- High efficiency driver with a power factor >.90 with input power of 120V 60Hz

• Modules fit most 3" recessed cans with **GU10** adapter**

- Long life LEDs up to 50,000 hours at 70% lumen maintenance
- No tools required for installation
- Tested in accordance with IESNA LM79 & LM80
- Optional GU10** adapter available

Electrical • Voltage : 120 VAC

• Current : 350mA

• Operation Temperature : $-30^{\circ}\text{C} \sim 40^{\circ}\text{C} (-22^{\circ}\text{F} \sim 104^{\circ}\text{F})$

• Warranty : Limited 5 years

CCT • 27K - 2700K

30K - 3000K40K - 4000K50K - 5000K

Listings • UL Classified

• Energy Star qualified

• Wet Rated

Trim Finishes • White standard, Black (BK), Silver (SV), and Bronze options available **











Series	Reflector	Mount	Watts	ССТ	Voltage	Finish
DL3	RB= Round Baffle RS= Round Smooth	23 = Quick Connect	9 = 9W	27K = 2700K 30K = 3000K 40K = 4000K 50K = 5000K	Z = 120VAC	W = White

Enter configuration: / Example: DL3-RB-23-9-30K-Z-W

Color Temp.	2700K	3000K	4000K	5000K
Lumens	590 Lm	680 Lm	730 Lm	780 Lm

^{**} Special Order

