

Project		Date
Type		
Model		

MWPK 17W LED Wall Pack

Product Description

The Luminoso MWPK Series combines traditional styling with the latest LED technology. The high pressure die cast housing along with anti-static powder painting makes this product ideal for exterior applications. The MWPK's highly efficient cooling system allows lower running temperatures translating into a maximized product life. The wall pack has a built in UL class driver and is also rated for damp and wet locations. Ideal for entry ways, area perimeters, stairwells and hallways this product offers the added security and cost effectiveness to meet any demand.

Features

Efficacy: 113 - 117 Lm/W
Power consumption: 17 Watts
Delivered Light Output: 1,900 - 1,950 Lumens
CRI: Ra>80
CCT: 4000K - 5000K
Input Voltage: 120 - 277 VAC
Input current: 0.33 - 0.14 Amps (120-277V)
THD: <20% (at 120V)
Power factor: > 0.9 (120V)
Lens: Polycarbonate optical lens
Mounting: J-Box or Direct wall mount w/ 1/2" entry at the bottom
Non-dimmable
Standard Lifetime: Designed to L70 minimum 50,000 hours
Operating temperature is -40°F to 104°F).



ACCESSORIES

Photocell

No. PC-JL-120-277V
USE: Photocell is field installed or pre-installed in factory by requesting



ORDER INFORMATION

EXAMPLE: MWPK-14-17W-40K-3M-Y-BZ



Series	Mount	Wattage	CCT	Optics	Voltage	Finish	Photocell
MWPK	14 = Direct Mount	17W	40K = 4000K 50K = 5000K	3M	Y = 120-277V	BZ = Bronze WH = White	Blank = standard PC=120-277V

Enter configuration:

** Special Order

PERFORMANCE DATA

WATTS	VOLTAGE	CRI	LUMENS 4000K	EFFICACY 4000K	LUMENS 5000K	EFFICACY 5000K
17W	120-277VAC	80	1,900	113lm/W	1,950	117lm/W

DIMENSIONS

