

Project		Date
Type		
Model		




ZHB Series LED High Bay

Features:

- Efficacy higher than 145lm/W, designed to replace 750W and 1000W HID.
- Die-cast aluminum housing, and polycarbonate diffuser.
- 120 degree lens guarantees light intensity and light uniformity.
- Hook for various applications.
- IP65 Rated / IK08 Rated
- Operating temperature is -20°F to 115°F.
- Power Factor: >0.9



Size	150W	200W
A:	8.9in	10.4in
B:	11.2in	12.6in
C:	5.8in	5.8in
D:	7.8in	7.8in



ORDER INFORMATION

EXAMPLE: ZHB-200W-50K-90D-Y-CL-MS



Series	Wattage	CCT	Beam	Voltage	Lens
ZHB	150W 200W	40K = 4000K 50K = 5000K	90D = 90°	Y = 120-277V	CL = Clear

Enter configuration:

PERFORMANCE DATA

Model	ZHB-150W	ZHB-200W
System Power	150W	200W
Voltage	120-277VAC	120-277VAC
Frequency	50/60Hz	50/60Hz
Lumen output	22,500lm	30,000lm
Diffuser material	Polycarbonate	Polycarbonate
Body material	Die-cast Aluminum	Die-cast Aluminum
Body color	Black	Black
LED type	SMD 2835	SMD 2835
CCT	4000K / 5000K	4000K / 5000K
CRI	>80	>80
SDCM	<5	<5
PF	>0.9	>0.9
Beam angel	60° / 90° / 120°	60° / 90° / 120°
Light Efficacy	150 Lm/W	150 Lm/W
IP Rating	IP65	IP65
IK Rating	IK08	IK08
Moutning	Hook suspension	Hook suspension
Ta	-20°F to 120°F	-20°F to 120°F
Certificate	UL	UL
Product Size	ø 11.2 x 7.8in	ø 12.6 x 7.8in
Carton Size	13 x 13 x 7.3in	14.4 x 14.4 x 7.8in
Qty / CTN	1pcs	1pcs